

Datasheet

Art.No. 73.300.0353.0

Female insert MIN BUS 3 2,5 40

revos MINI 3 pole + ground, female insert, 400V/10A, screw connection



Art.No.	73.300.0353.0
EAN	4015573229396
Order unit	10 pieces

Approvals



Technical data

General

Model	Female insert
Inflammability class of insulation material acc. with UL94	V2
Colour	Grey
Mating cycles	50
Pollution degree	3
Modular version	No
Operating temperature range min.	-40 °C
Operating temperature range max.	120 °C

Connection Data

Connection type	Screw connection
Number of poles	3
Total number of poles (without ground contact)	3
With wire protection	No
Min. conductor diameter rigid (solid/stranded)	0.5
Max. conductor diameter rigid (solid/stranded)	2.5
Protective contact	Yes

Technical Data UL/CSA

Rated voltage according to UL/CSA	600
Rated current according UL	10
Rated current according CSA	10
Min. conductor cross section flexible wire	0.5

Max. conductor cross section flexible wire	2.5
Conductor cross section flexible AWG wire	22-12 AWG

Model

With housing	No
--------------	----

Contacts

Contact material	Copper alloy
Surface	Tin-plated
Contact resistance	2 mOhm
Wire strip length	4 mm

Screws head design/recomm. Torque

Mounting screws	M3/0.5-0.7 Nm Slot
Clamping screws	M3/0.5-0.7 Nm Slot
Ground conductor screws	M3/0.5-0.7 Nm Slot

Technical Data DIN EN 61984

Nominal voltage	400
Rated voltage face/ground	250
Nominal current	10
Rated impulse voltage	4 kV

Drawings

Draht führt wieder bei Änderung besonders geprüft.
 Ansicht ist in Führung.
 MIT F. GRUNDZEICHEN/BEZ. MIT F. 10.0000.0000.0000.0000

mit Schraubanschluß
with screw connection

Freileitersch nach		CND - Zeichnung, keine massiven Änderungen			1. Verwendung: -		Bl.: 1 von 1	
/	Maßstab	Werkstoff und Oberflächen:		2003	Tag	Zeichnung Nr.		Index
/	2:1			Entworfen	11.07.	73.300.0353.0 01K		
/				geprüft	-			
/	Vol.	mm ³	Stk.	mm ³	Nenngr.	Ersatz für:		
/								
wieland Elektrische Verbindungen		Typ MIN BUS 3 2,5 40		Benennung BUCHSENE INSATZ 3-polig SOCKET INSERT 3-pole				
Änderung								

733000035301K_4 CAD/K20 Bauer 23.07.2005 08:33:22 1,000