


Data sheet

Commercial Art.No.: 70.300.3253.0

female insert BAS BUS 32 2,5 50

Female insert revos basic, 32-poles, rated current: 16A, rated voltage:500V, with tin-plated contacts



Commercial Art.No.	70.300.3253.0
EAN	4015573320093
Order Unit	1

certificates / approvals



Technical data

general

model	female insert
inflammability class of insulation material acc. with UL94	V0
color	grey
mating cycles	200
pollution degree	3
suitable for modular version	no
operating temperature range min.	-40 °C
operating temperature range max.	120 °C

connection data

connection type	screw connection
number of poles	32
plus switching contacts	0
number of pole for rated current 2	0
number of pole for rated current 3	0
total number of poles (without ground contact)	32
with wire protection	yes
min. conductor diameter rigid (solid/stranded)	0.5 mm ²
max. conductor diameter rigid (solid/stranded)	2.5 mm ²
protective contact	yes

technical data UL/CSA

nominal voltage according to UL/CSA	600 V
-------------------------------------	-------

nominal current according UL	16 A
nominal current according CSA	16 A
min. conductor cross section flexible wire	0.5 mm ²
max. conductor cross section flexible wire	2.5 mm ²
conductor cross section flexible AWG wire	22-14 AWG

model

with housing	no
--------------	----

contacts

contact material	copper alloy
surface	tin-plated
contact resistance	≤ 1.5 mOhm
wire strip length	7 mm

screws head design/recomm. Torque

mounting screws	H1/0.5-0.7 Nm
clamping screws	H1/0.5-0.7 Nm
ground conductor screws	H2/1.2-1.6 Nm

technical data DIN EN 61984

nominal voltage	500 V
nominal voltage face/ground	500 V
nominal current	16 A
rated impulse voltage	6 kV


classification

ECLASS 11	
ECLASS 8.1	27440205
ETIM 9.0	EC000438
ETIM 8.0	EC000438
ETIM 7.0	EC000438
ETIM 6.0	EC000438
ETIM 5.0	EC000438
ETIM 4.0	EC000438
ETIM 3.0	EC000438


product compliance

ROHS conformity status	compliant/exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1

Farbe und Kennzeichnung siehe 70.300.1640.0
 colour and marking see 70.300.1640.0



Ansicht in Richtung Buchsenkontakte (Steckseite)
view in direction to the socket contact



32-polig mit Schraubanschluß und Drahtschutz
 32-pole with screw connection and wire protection



Diese Maße werden bei Abnahme besonders geprüft

Ausschließlich Prüfmaße

Mit z.E. gekennzeichnete Maße sind nur für interne Zwecke gültig



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited.

Freitoleranz nach		CAD - Zeichnung, keine manuellen Änderungen			1. Verwendung: -		Bl.: 1 von 1		
	/	Maßstab 1:1	Werkstoff und Oberfläche:		2003	Tag	Name	Zeichnung Nr. 70.300.3253.0 01K	Index
	/		Farbe: kieselgrau colour: pebble grey		Entworfen	09.07.	Bauer F.		
	/				Geprüft	-	-		
	/	Vol.	mm ²	Offl.	mm ²	Normgepr.	-	Ersatz für: -	
	/	wieland Elektrische Verbindungen		Typ BAS BUS 32 2,5 50		Benennung BUCHSENE INSATZ SOCKET INSERT 2,5qmm 500V 16A			
Buchstabe	Datum / Blatt								
Änderung									