

Datasheet

Art.No. 96.052.4153.1

Male connector with strain relief RST20I5S S1 ZR2 V SW

Connector RST20i5, 5 pole, male, screw connection, 250/400V, 20A, for cable diameters 10-14 mm, color of coding: black, color of housing: black



Art.No.	96.052.4153.1
EAN	4015573862142
Order unit	1 pieces

Approvals



Technical data

General

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	3
Mechanical coding	Yes
Interlockable	Yes
Color of coding/ contact carrier	Black
Marking of poles	3, N, PE, 2, 1

Connection Data

Connection cross section solid	4 mm ²
Connection cross section stranded	4 mm ²
Terminations per pole	1

Model

Model	male
Number of poles	5
Connection type	Screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69K

Material

Housing material	Polyamide
------------------	-----------

Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Dimensions

Length	80.4 mm
Width	34.6 mm
Height	34.6 mm

Drawings

Auslieferungszustand

for cable diameter 10-14mm
für Kabeldurchm. 10-14mm

Verpackungseinheit: je 100 Stück
packaging unit: per 100

M1:1

A-A

Teil-Nr./ part-nf.	Farbe/ color:	Type
96.052.4153.1	schwarz, ähnl. RAL 9005/ black, similar to RAL 9005	RST2015S SI ZR2 V SW
96.052.4153.0	lichtgrau, ähnl. RAL 7035/ lightgrey, similar to RAL 7035	RST2015S SI ZR2 V 6L

Beschreibung Description RST2015S SI ZR2 V SW		Zeichnung Nr. / Drawing No.	Blatt / Sheet
Material / Material		Stückzahl / Quantity	Fertigung / Production
Hersteller / Manufacturer		Datum / Date	Version / Version
Zeichnung / Drawing		Blatt / Sheet	Stückzahl / Quantity
Hersteller / Manufacturer		Datum / Date	Version / Version

STECKERTEIL MIT ZUGENTLASTUNG
 PLUG PART WITH TENSIONING
 STECKERTEIL MIT ZUGENTLASTUNG
 PLUG PART WITH TENSIONING